

Trauma Implant System

A Jointless Joint



MEDI ORTHO LINK

Bringing Life Back To Your Bones



Cat. 101

Length : 60 mm To 150 mm

AUSTIN MOORE PIN WITH 2 NUTS



Cat. 106

Length : 6.5 mm :- 35 mm To 120 mm
7.0 mm :- 40 mm To 125 mm

CANNULATED CANCELLOUS SCREW HEX
Dia.: 6.5 mm, 7.0 mm (32mm Thread)



Cat. 101.s

Length : 33 mm, 35 mm, 37 mm,
39 mm, 41 mm

SHOULDER PROSTHESIS



Cat. 107

Length : 35 mm To 120 mm

CANNULATED CANCELLOUS SCREW HEX
Dia.: 6.5 mm, 7.0 mm (Fully Thread)



Cat. 102

Dia. : 37 mm To 55 mm

AUSTIN MOORE PROSTHESIS XL



Cat. 108

WASHER FOR C.C. & CANCELLOUS SCREW
Small 4.0 mm, Large 6.5 mm



Cat. 103

Length : 14 mm To 35 mm
40 mm To 80 mm

CANNULATED CANCELLOUS SCREW HEX
Dia.: 4.0 mm (16 mm Thread)



Cat. 109

Length : 50 mm To 120 mm

D.H.S. LEG SCREW (A.O. TYPE)



Cat. 104

Length : 14 mm To 35 mm
40 mm To 80 mm

CANNULATED CANCELLOUS SCREW HEX
Dia.: 4.0 mm (Fully Thread)



Cat. 109.P

Length : 50 mm To 80 mm

PEDIATRIC D.H.S. LEG SCREW (A.O. TYPE)



Cat. 105

Length : 25 mm To 120 mm

CANNULATED CANCELLOUS SCREW HEX
Dia.: 6.5 mm, 7.0 mm (16 mm Thread)



Cat. 110 Hole : 03 To 14
D.H.S. SHORT/LONG BARREL PLATE (ROUND HOLE) A.O. TYPE
Angle : 120° To 150°



Cat. 112.T Hole : 04
TROCHANTERIC STABILIZATION PLATE FOR D.H.S.



Cat. 111 Hole : 03 To 12
D.H.S. LONG/SHORT BARREL PLATE (D.C.HOLE) A.O. TYPE
Angle : 125° To 140°



Cat. 113 Hole : 05 To 16
95° ANGLE BLADE PLATE (ROUND HOLE) A.O. TYPE
Blade Length :60 mm To 80 mm



Cat. 111.D Hole : 04 To 06
D.H.S. PEDIATRIC PLATE (D.C.HOLE) A.O. TYPE
Angle : 120°



Cat. 114 Hole : 05 To 16
95° ANGLE BLADE PLATE (D.C. HOLE)
Blade Length :60 mm To 80 mm



Cat. 111.P Hole : 03 To 06
D.H.S. PEDIATRIC PLATE (D.C.HOLE) A.O. TYPE
Angle : 130° To 135°



Cat. 114.D55-70 Hole : 04 To 06
120° ANGLE BLADE PLATE (D.C.)
Blade Length :55 mm To 70 mm



Cat. 112 Hole : 04,05,06
D.H.S. PLATE S.B./L.B. (TROCHANTERIC SUPPORT) ROUND HOLE
Angle : 130° To 135°



Cat. 115 Hole : 05 To 18
95° D.C.S. BARREL PLATE (ROUND HOLE)



Cat. 112.D Hole : 04,05,06
D.H.S. PLATE S.B./L.B. (TROCHANTERIC SUPPORT) DC HOLE
Angle : 130° To 135°



Cat. 116 Hole : 05 To 14
95° D.C.S. BARREL PLATE (D.C. HOLE)



Cat. 117

Hole : 04 To 12

1/3 TUBULAR PLATE



Cat. 121.03

Hole : 02 To 08

SMALL "T" PLATE (HEAD 03 HOLE)



Cat. 118

Hole : 04 To 12

SMALL D.C. PLATE



Cat. 121.04

Hole : 02 To 08

SMALL "T" PLATE (HEAD 04 HOLE)



Cat. M118

Hole : 05 To 12

LM SMALL D.C. PLATE



Cat. 122

Hole : 02 To 08

OBLIQUE "T" PLATE



Cat. 118.H

Hole : 04 To 12

HOOK PLATE



Cat. 123

Hole : 03 To 16

RECONSTRUCTION PLATE (ROUND HOLE)
For 3.5 mm Screw



Cat. 119

Hole : 04 To 12

SMALL L.C.D.C. PLATE



Cat. 123.PC

Hole : 04 To 14
(2 Hole Variation)

PELVIC CURVED PLATE 3.5 MM
For 3.5 mm Screw



Cat. 120

Hole : 02 To 06

ELLIS PLATE



Cat. 123.PC

Hole : 04 To 20
(2 Hole Variation)

PELVIC STRAIGHT PLATE 3.5 MM
For 3.5 mm Screw



Cat. 123.S

PELVIC SYMPHYSEAL PLATE 3.5 MM
For 3.5 mm Screw

Hole : 04 , 06 Hole



Cat. 127

NARROW L.C.D.C. PLATE

Hole : 04 To 14



Cat. 124

RECONSTRUCTION PLATE (D.C. HOLE)
For 3.5 mm screw

Hole : 03 To 16



Cat. 128

BROAD D.C. PLATE

Hole : 06 To 16



Cat. 124.C

RECONSTRUCTION PLATE CURVED (D.C. HOLE)
For 3.5 mm screw

Hole : 04 To 14
(2 Hole Variation)



Cat. 129

BROAD L.C.D.C. PLATE

Hole : 06 To 12



Cat. 125

SEMI TUBULAR PLATE

Hole : 04 To 12



Cat. 130

T BUTTRESS PLATE

Hole : 03 To 12



Cat. 126

NARROW D.C. PLATE

Hole : 04 To 14



Cat. 130.H

T BUTTRESS PLATE (HUMERUS)

Hole : 04 To 10



Cat. M126

LM NARROW D.C. PLATE

Hole : 06 To 14



Cat. 131

L BUTTRESS PLATE LEFT & RIGHT

Hole : 03 To 12



Cat. 132
LATERAL TIBIAL PLATE LEFT & RIGHT

Hole : 04 To 12



Cat. 138
RECONSTRUCTION PLATE (D.C. HOLE)
For 4.5 mm screw

Hole : 03 To 16



Cat. 133
COBRA PLATE

Hole : 05 To 12



Cat. 134
CLOVERLEAF PLATE

Hole : 04 To 12



Cat. 135
CONDYLAR BUTTRESS PLATE LEFT & RIGHT

Hole : 04 To 16



Cat. 136
SHERMAN Y PLATE

Hole : (3 X 3 X 3 To 3 X 3 X 10)
(4 X 4 X 4 To 4 X 4 X 10)



Cat. 137
RECONSTRUCTION PLATE (ROUND HOLE)
For 4.5 mm screw

Hole : 03 To 16

Bone Screws



Cat. 139

Length : 12 mm To 60 mm
65 mm To 85 mm

CORTICAL SCREW HEX
Dia.: 3.5mm (20 T. P. I.)



Cat. 144

Length : 25 mm To 120 mm

CANCELLOUS SCREW HEX
Dia. 6.5 mm (16 mm Thread)



Cat. 140

Length : 12 mm To 50 mm

CORTICAL SCREW HEX
Dia.: 3.5mm (14 T. P. I.)



Cat. M144

Length : 25 mm To 110 mm (With Head)

LM CANCELLOUS SCREW
Dia. 6.5 mm X 16TH.



Cat. 141

Length : 16 mm To 70 mm

CORTICAL SCREW HEX
Dia.: 4.5mm (14 T. P. I.)



Cat. 145

Length : 35 mm To 120 mm

CANCELLOUS SCREW HEX
Dia. 6.5 mm (32 mm Thread)



Cat. M141

Length : 20 mm To 62 mm (With Head)

LM CORTICAL SCREW HEX (SELF TAPPING)
Dia.: 4.5mm (14 T. P. I.)



Cat. M145

Length : 35 mm To 110 mm (With Head)

LM CANCELLOUS SCREW
Dia. 6.5 mm X 32TH.



Cat. 142

Length : 14 mm To 35 mm
40 mm To 80 mm

CANCELLOUS SCREW HEX
Dia.: 4.0 mm (16 mm Thread)



Cat. 146

Length : 35 mm To 120 mm

CANCELLOUS SCREW HEX
Dia. 6.5 mm (Fully Thread)



Cat. 143

Length : 14 mm To 35 mm
40 mm To 80 mm

CANCELLOUS SCREW HEX
Dia. 4.0 mm (Fully Thread)



Cat. M146

Length : 35 mm To 110 mm (With Head)

LM CANCELLOUS SCREW
Dia. 6.5 mm X Fully Thread



Cat. 147

Length : 25 mm To 100 mm

MALLEOLER SCREW HEX
Dia.: 4.5 mm



Cat. 148

Length : 16 mm To 30 mm
32 mm To 44 mm

I.L. BOLT 2.9 mm HEX
For 6 mm Humerus I.L. Nail



Cat. 149

Length : 20 mm To 32 mm
34 mm To 50 mm

I.L. BOLT 3.4 mm HEX
For 7, 8 mm Humerus I.L. Nail



Cat. 150

Length : 20 mm To 34 mm
36 mm To 60 mm

I.L. BOLT 3.9 mm HEX
For 08 mm I.L. Nail



Cat. 151

Length : 20 mm To 100 mm

I.L. BOLT 4.9 mm HEX
For 09 mm To 13 mm I.L. Nail



Cat. 152

Length : 12 mm To 34 mm

HERBERT SCREW
(HEAD - 4.5 mm & TAIL - 3.5 mm)



Cat. 153

Length : 00 mm, 05 mm

CAP FOR HUMERUS NAIL

Intramedullary Nail



Cat. 154

Length : 20 cm To 30 cm

INTERLOCKING NAIL FOR HUMERUS IN 1 C.M. VARIATION
(SOLID & CANULATED)
Dia.: 6,7,8 mm



Cat. 157.S

Length : 22 cm

SHORT RE-CON NAIL
Dia.: 09 mm To 12 mm



Cat. 155.13

Length : 28 cm To 38 cm

INTERLOCKING NAIL FOR TIBIA IN 1 C.M. VARIATION
(13 mm Design)
Dia. 08 mm To 11 mm



Cat. 158

Length : 34 cm To 44 cm

K - NAIL FOR FEMUR
Dia.: 08 mm To 12 mm



Cat. 155.D

Length : 285 mm To 405 mm

INTERLOCKING NAIL FOR TIBIA (DISTAL JIG)
IN 1.5 C.M. VARIATION
Dia. 08 mm To 11 mm



Cat. 160

Length : 18 cm To 34 cm

RUSH NAIL
Dia.: 1.5 mm To 4.0mm



Cat. 156.13

Length : 34 cm To 44 cm

INTERLOCKING NAIL FOR FEMUR IN 2 C.M. VARIATION
(13 mm Design)
Dia. 09 mm To 12 mm



Cat. 161

Length : 18 cm To 34 cm

SQUARE NAIL FOR RADIUS & ULNA
Dia.: 2.0 mm TO 4.0 mm



Cat. 156.D

Length : 330 mm To 450 mm

INTERLOCKING NAIL FOR FEMUR IN 1.5 C.M. VARIATION
(DISTAL JIG)
Dia. 09 mm To 12 mm



Cat. 162

Length : 14 cm To 46 cm

ENDER'S NAIL
Dia.: 2.0 mm To 4.5 mm



Cat. 157

Length : 34 cm To 44cm

RE-CON NAIL - RIGHT & LEFT IN 2 C.M. VARIATION
Dia.: 09 mm To 12 mm



Cat. 165

Hole : 05, 08, 11

CERVICAL H SPINAL PLATE



Cat. 166

Length : 04", 06", 09", 12"

"K" WIRE (DOUBLE ENDED)
Dia.: 0.8 mm To 3.0 mm



Cat. 165.W

WASHER SPIKE



Cat. 167

Length : 06", 09"

THREADED "K" WIRE
Dia.: 1.0 mm To 3.0 mm



Cat. 168

Length : 20 cm To 40 cm

"L" WIRE (LAMBRINUDI)
Dia.: 1.5 mm To 4.5 mm



Cat. 169

Size : 16 swg To 26 swg

S.S. WIRE REEL



Cat. 169.L

Size : 16 swg To 26 swg

S.S. WIRE LOOP (04 mtr)



Cat. 171

Size : 0.8, 1.0, 1.2, 1.5 mm

CERCLAGE WIRE

Staples



Pins & Screws For External Fixator



Cat. 172

Length : 10 mm To 30 mm

"U" TYPE STAPLES
Dia.: 1.5 mm To 3.0 mm



Cat. 174

Length : 06", 07", 09"

STEINMAN PIN
Dia.: 3.0 To 4.5 mm • 5.0 To 6.0 mm



Cat. 173

COVENTARY STAPLES
Small / Medium / Large



Cat. 174.D

S.T. PIN FOR DISTAL DEVICE
Dia.: 2.5 , 3.0 , 3.5 mm



Cat. 175

Length : 09"

DENHAM PIN
Dia.: 4.0 mm To 5.0 mm



Cat. 176

Length : 04" To 08"

SCHANZ SCREW
Dia.: 2.0 mm To 5.0 mm



Cat. 176.C

Length : 09"

SCHANZ SCREW (CANCELLOUS THREAD 6.5 mm)
Dia.: Shaft Dia. 4.5 mm (16" & 32")



Cat. 176.S

Length : 06", 08"

SELF DRILLING SCHANZ SCREW
Dia.: 4.5 mm, 5.0 mm



Cat. 176.T

Length : 06", 08"

TAPPER THREAD SCHANZ SCREW
Dia.: 6.0 mm (32 & 52 Thread)



Cat. 180

Length : 25 cm

PROXIMAL FEMORAL NAIL SHORT (P.F.N.)
Dia. : 09, 10, 11, 12 mm (130° & 135°)



Cat. 176.THA4060

Length : 07"

SCHANZ PIN TAPPER.TH.(HA COATED)
40THX6.0 MM



Cat. 180.L/R

Length : 34 cm To 44 cm

PROXIMAL FEMORAL NAIL LEFT & RIGHT (P.F.N.)
Dia. : 09, 10, 11, 12 mm



Cat. 176.THA5260

Length : 07"

SCHANZ PIN TAPPER.TH.(HA COATED)
52THX6.0 MM



Cat. 181

Length : 15 cm To 30 cm

SUPRA CONDYLAR NAIL (I.M.S.C.)
Dia. : 10, 11, 12, 13 mm



Cat. 177

Length : 10"

HIP TRACTION SCREW
Dia.: 4.5,6.5,8.0 mm



Cat. 182

Length : 0 mm, 05 mm, 10 mm

CAP FOR RECON, P.F.N., I.M.S.C., CYRUS NAIL
13mm DESIGN TIBIA & FEMUR NAIL



Cat. 178

Length : 50 mm To 120 mm

PROXIMAL BOLT 8.0 MM (FOR P.F.N., T.F.N. NAIL)



Cat. 183

Length : 0 mm, 05 mm, 10 mm

CAP FOR TIBIA & FEMUR NAIL



Cat. 179

Length : 50 mm To 120 mm

PROXIMAL BOLT 6.4 MM
(FOR P.F.N., T.F.N., RECON, CYRUS FEMUR NAIL)



Cat. 184

Length : 28 cm To 38 cm

INTERLOCKING NAIL FOR TIBIA SOLID IN 2 C.M. VARIATION
Dia.: 08,09,10 mm



Cat. 185 Length : 34 cm To 44 cm
INTERLOCKING NAIL FOR FEMUR SOLID IN 2 C.M. VARIATION
Dia.: 09 mm To 12 mm



Cat. 191 Length : 28 cm To 38 cm
MULTIFUNCTION TIBIA NAIL
Dia. 08,09,10 mm



Cat. 186 Length : 28 cm To 38 cm
CYRUS TIBIA IN 2 C.M. VARIATION
Dia. 08 mm To 10 mm



Cat. 192 Length : 60 To 120 mm
PROFAAN BLADE



Cat. 187 Length : 34 cm To 44 cm
CYRUS FEMUR IN 2 C.M. VARIATION (LEFT & RIGHT)
Dia. 09 mm To 12 mm



Cat. 193 Length : 170,200,240 mm
PROFAAN 130*
Dia. :- 09 To 12 mm



Cat. 188 Length : 28 cm To 38 cm
TIBIA NAIL (UPPER BEND)
Dia. 08 mm To 10 mm



Cat. 193.L/R Length : 32 To 44 cm
PROFAAN LONG 130*
Dia. :- 09 To 12 mm



Cat. 189 Length : 18 cm
TROCHANTERIC FEMORAL NAIL (T.F.N.)
Dia. 09, 10, 11, 12 mm (130° & 135°)



Cat. T196.L/R Length : 34 To 44 cm
T196 TIT ANTEGRADE FEMORAL NAIL
Dia. :- 09 To 11 mm



Cat. 190 Length : 44 cm
ELASTIC NAIL
Dia. 2.0, 2.5, 3.0, 3.5, 4.0, 4.5 mm

Mini Plate & Screw (Dai. 1.5,2.0,2.5 mm)



Cat. S101/TS101

Hole : 02 To 20

MINI STRAIGHT PLATE (WITHOUT GAP)



Cat. S107/TS107

MINI "X" PLATE



Cat. S101.G/TS101.G

Hole : 02 To 10

MINI STRAIGHT PLATE (WITH GAP)

Left



Right



Cat. S108/TS108

MINI "Z" PLATE (LEFT & RIGHT)

Hole : 04



Cat. S102/TS102

Hole : 02 To 03

MINI "T" PLATE SMALL (WITH HEAD 2 HOLE & 3 HOLE)



Cat. S109/TS109

Hole : 04 , 06

MINI CURVED PLATE (LEFT & RIGHT)



Left

Cat. S103/TS103

Hole : 02 To 03

MINI "L" PLATE 90° (LEFT & RIGHT)



Right



Left

Cat. S110/TS110

Hole : 04,06

MINI ANGULAR PLATE 150° (LEFT & RIGHT)



Right



Cat. S105/TS105

Hole : 06

MINI "I" PLATE



Cat. S111/TS111

Hole : 04 , 06

MINI ORBITA PLATE (WITH GAP)



Cat. S106/TS106

Hole : 5 To 6

MINI "Y" PLATE (SINGLE & DOUBLE)



Cat. S112/TS112

Hole : 04 , 06

MINI ORBITA PLATE (WITHOUT GAP)



Cat. S113/TS113

Hole : 02 To 20

MINI RECONSTRUCTION PLATE



Cat. S120/TS120


Hole : 20 To 24

ANGLE RECONSTRUCTION PLATE LEFT & RIGHT



Cat. S114/TS114

MINI NOSE PLATE ("H" SHAPE)



Cat. S122/TS122

1" X 1"

WIRE MESH



Cat. S114/TS114

MINI NOSE PLATE ("Y" SHAPE)



Cat. TS122.P

060" X 060", 060" X 080" MM
100" X 100", 120" X 120" MM
120" X 150", 120" X 180" MM

PRE BENDED MESH



Cat. S115/TS115

MINI 3D SQUARE PLATE



Cat. TS123

TIT ORBITAL FLOOR MESH

EXTRA SMALL, SMALL, BIG



Cat. S116/TS116

MINI CHIN PLATE



Cat. S123

ARCH BAR

1 FEET



Cat. S117

Hole : 04 To 10

DYNAMIC COMPRESSION PLATE (D.C.P.),
PLATE FOR 2.5 & 2.7 MM SCREW



Cat. P121.S

PEEK CERVICS SPACER WITH SCREW (STERILE)

5", 6", 7", 8"

Mini Plate & Screw (Dai. 1.5,2.0,2.5 mm)



External Fixator



Cat. S130/TS130

Length : 04 mm To 12 mm

MINI SCREW 1.5 mm SLOT



Cat. S131/TS131

Length : 04 mm To 14 mm

MINI SCREW 2.0 mm SLOT (32 TPI)



Cat. S132/TS132

Length : 06 mm To 16 mm

MINI SCREW 2.5 mm SLOT (32 TPI)



Cat. S133

Length : 06mm To 14mm

I.M.F. (INTRA MAXILLARY FIXATION) SCREW SLOT



Cat. S140.25/T140.25

Length : 08 mm To 30 mm

CORTICAL SCREW 2.5 mm HEX (24 TPI)



Cat. S140.27/T140.27

Length : 10 mm To 34 mm

CORTICAL SCREW 2.7 mm HEX (24 TPI)



Cat. 201.001

Size : 4.5 X 8.0 mm

AESCULAP CLAMP



Cat. 201.002

Size : 8.0 X 8.0 mm

ROD TO ROD CLAMP



Cat. 201.003

Size : 04" TO 16"

CONNECTION ROD

Dia.: 8.0 mm



Cat. 202.001

Size : 2.5 X 4.0 mm

AESCULAP CLAMP



Cat. 202.002

Size : 4.0 X 4.0 mm

AESCULAP CLAMP



Cat. 202.003

Size : 4" To 16"

CONNECTION RODS

Dia.: 4.0 mm



Cat. 203.001

Size : 4.5 X 11 mm

A.O. TYPE CLAMP



Cat. 203.006C

UNIVERSAL JOINT WITH 2 CLAMP



Cat. 203.001

Size : 6.0 X 11 mm

A.O. TYPE CLAMP



Cat. 203.006

UNIVERSAL JOINT FOR TWO ROD



Cat. 203.002

Size : 11 X 11 mm

ROD TO ROD CLAMP



Cat. 203.007

TRANSVERSE CLAMP PIN ADJUSTABLE



Cat. 203.003

Length : 6" To 18"

CONNECTION RODS
Dia.: 11 mm



Cat. 203.009

Size : FOR 4.5 & 6.0 mm

T-HANDLE FOR SCHANZ SCREWS / STEINMAN PIN



Cat. 203.004

Size : 4.5 X 11 mm

A. O. TYPE DOUBLE PIN CLAMP



Cat. 203.011

THREADED ROD WITH 3 TUBE & NUTS (D.A.)



Cat. 203.005

Size : 4.5 X 11 mm

OPEN CLAMP



Cat. 204.001

Size : 2.5 X 4.0 mm

A. O. TYPE CLAMP



Cat. 204.002
A. O. TYPE CLAMP

Size : 3.5 X 4.0 mm



Cat. 209
5/8 RING

Length : 130 mm To 200 mm



Cat. 204.003
A. O. TYPE CLAMP

Size : 4.0 X 4.0 mm



Cat. 210
ITALIAN FEMORAL ARCHES
Angle :- 90°, 120°

Length : 140 mm To 200 mm



Cat. 205.001
BALL TYPE CLAMP



Cat. 211
THREADED ROD (06 mm)

Length : 100 mm To 400 mm



Cat. 205.002
DISTRACTOR UNIT

Length : 6" To 12"



Cat. 211.S
THREADED ROD SLOTTED (06 mm)

Length : 60 mm To 80 mm



Cat. 205.003
BALL & SOCKET SPANNER



Cat. 212
TELESCOPIC ROD

Length : 100 mm To 250 mm



Cat. 207
HALF RING

Length : 80 mm To 220 mm



Cat. 212.G
TELESCOPIC ROD GRADUATED

Length : 80 mm To 120 mm



Cat. 213.001
HINGES (MALE END 1 HOLE)



Cat. 214.M
POST MALE

Hole : 01 To 04



Cat. 213.002
HINGES (FEMALE END 1 HOLE)



Cat. 214.F
POST FEMALE

Hole : 01 To 04



Cat. 213.003
90 DEGREE HINGES



Cat. 215
OBLIQUE SUPPORT



Cat. 213.SM
SINGLE JOINT M TO F



Cat. 216
CURVED PLATE



Cat. 213.SF
SINGLE JOINT F TO F



Cat. 217.S
SHORT CONNECTION PLATE

Hole : 02 To 07



Cat. 213.U
UIVERSAL JOINT



Cat. 217.L
LONG CONNECTION PLATE

Hole : 08 To 10



Cat. 217.T

Hole : 01 To 03

TWISTED PLATE



Cat. 218.001

CONNECTING BOLT



Cat. 218.002

NUT



Cat. 218.002.S

SQUARE NUT



Cat. 218.003
WIRE FIXATION BOLT (SIDE SLOTTED)



Cat. 220 Length : 1.8 mm X 16"
TENSION K-WIRE (TROCER TIP & BIONET TIP)



Cat. 218.004
WIRE FIXATION BOLT (CENTRE HOLE)



Cat. 221 Length : 1.8 mm X 16"
OLIVE WIRE (BINET & TROCER TYPE)



Cat. 218.005
MULTIPLE PIN FIXATION BOLT



Cat. 221
OLIVE WIRE (BINET & TROCER SEAMLESS TYPE)



Cat. 218.006 Size : For 4.5 & 6.0 mm
SINGLE PIN FIXATION BOLT



Cat. 222.001
WASHER (SIMPLE)



Cat. 218.008 Hole : 01 To 04
WRENCHO CUBE



Cat. 222.002
WASHER (SLOTTED)



Cat. 219.002 Size : 30 mm To 60 mm
THREADED SOCKET



Cat. 222.003
WASHER (CONICAL COUPLE)



Cat. 223.001
WIRE TENSIONERS (SIMPLE)



Cat. 206.001
ALPHA CLAMP 06 X 10 mm



Cat. 223.002
WIRE TENSIONERS (GRADUATED)



Cat. 206.002
BETA CLAMP 08 X 12 mm



Cat. 224
Length : 6 mm To 11 mm
SPANNER ORDINARY



Cat. 206.003
BETA CLAMP 08 X 15 mm



Cat. 225
Length : 8,10,11 mm
T-HANDLE SPANNER



Cat. 206.004
BETA CLAMP ADD ON



Cat. 217.TE
Size : 5H, 7H, 9H, 11H
CONNECTION PLATE WITH THREADED END



Cat. 206.005
Length : 100 mm x 60 mm x 100 mm
SINGLE PIN DISTRACTOR



Cat. 206.006
Length : 100 mm x 150 mm
200 mm
DOUBLE PIN DISTRACTOR (M4)



Cat. 206.006.B Length : 150 mm , 200 mm , 250 mm , 300 mm
DOUBLE PIN DISTRACTOR (M6)



Cat. 206.012 Length : 200 mm , 250 mm , 300 mm , 350 mm , 400 mm
STRAIGHT ROD 4.0 MM



Cat. 206.007 Length : 150 mm , 200 mm , 250 mm , 300 mm
FISH MOUTH DISTRACTOR



Cat. 206.013 Size : 2.5 mm (35 x 35 mm)
SMALL "L" ROD 3.0 mm (50 x 50 mm)
4.0 mm (75 x 75 mm)



Cat. 206.008 Length : 50 X 75 mm
PIP DISTRACTOR



Cat. 206.014 Size : 2.5 mm (50 x 50 mm)
LARGE "L" ROD 3.0 mm (60 x 60 mm)
4.0 mm (90 x 90 mm)



Cat. 206.009 Length : 75 mm , 100 mm , 150 mm
STRAIGHT ROD 2.0 MM



Cat. 206.015 Size : 2.5 mm (60 x 45 x 60 mm)
"Z" ROD 3.0 mm (80 x 50 x 80 mm)
4.0 mm (100 x 60 x 100 mm)



Cat. 206.010 Length : 75 mm , 100 mm , 150 mm , 200 mm , 250 mm
STRAIGHT ROD 2.5 MM



Cat. 206.016 Dia : 2 , 3 mm
ALLEN KEY



Cat. 206.011 Length : 100 mm , 150 mm , 200 mm , 250 mm , 300 mm
STRAIGHT ROD 3.0 MM



Cat. T103
Length : 14 mm To 35 mm
40 mm To 80 mm
TIT CANNULATED CANCELLOUS SCREW HEX (C.C.SCREW)
Dia.: 4.0 mm (16 mm Thread)



Cat. T199
Tit Eight Plate
Length : Small ,Medium, Large



Cat. T104
Length : 14 mm To 35 mm
40 mm To 80 mm
TIT CANNULATED CANCELLOUS SCREW HEX (C.C.SCREW)
Dia.: 4.0 mm (Fully Thread)



Cat. T199.D
Tit Eight Dynamic
Compression PLate
Length : 12mm, 16mm, 20mm



Cat. T142
Length : 14 mm To 35 mm
40 mm To 80 mm
CANCELLOUS SCREW HEX
Dia.: 4.0 mm (16 mm Thread)



Cat. T143
Length : 14 mm To 35 mm
40 mm To 80 mm
CANCELLOUS SCREW HEX
Dia. 4.0 mm (Fully Thread)

